

UPHOLSTERY 9935 TWILIGHT



5031 Brass



5100 Hemp



5040 Sky



5090 Cotton



5060 Lapis



5101 Lily Pad



5080 Angora



5010 Cocoa



5130 Aquamarine



5020 Merlot

UPHOLSTERY 9936 WHIRL*



5040 Caramel



5030 Gold



5080 Linen



5070 Cadet



5021 Rust



5011 Chestnut



5061 Pesto



5130 Sangria



5140 Shadow



5091 Spinach

Upholstery Specifications

Style	9935 Twilight
Contents	65% post-consumer recycled polyester 18% pre-consumer recycled nylon 17% nylon
Weight	8.8 ± 1.0 oz./lin. yd.
Width	54" min. useable
Repeat	4.5" vertical and horizontal
Backing	SBR backcoating
Treatment	BLOCKaide® stain repellent

Cleaning Code	W-S
	Standard Care Label W-S. Clean with water based cleaning agents, foam or pure, water free solvents. Vacuuming or light brushing is recommended to prevent dust and soil buildup.

Performance	
Breaking strength (ASTM D5034)	175 lbf min. warp and 130 lbf min. fill
Seam Slippage (ASTM D4034)	55 lbf min. warp and 40 lbf min. fill
Pilling resistance (ASTM D3511)	Class 4 min.
Colorfastness to light (AATCC 16 Option 3)	Grade 4 min. at 40 hours
Colorfastness to crocking (AATCC 8)	Grade 4 min. dry, Grade 3 min. wet
Abrasion resistance (ASTM D4157)	50,000 double rubs min. - cotton duck

Flammability	
State of CA. Tech. Bulletin, 117-2013 SEC. I	Passes
NFPA 260	Class I

Style	9936 Whirl*
Contents	52% pre-consumer recycled polyester 48% post-consumer recycled polyester
Weight	10.9 ± 1.0 oz./lin. yd.
Width	54" min. useable
Repeat	2.25" vertical, 3.6" horizontal
Backing	SBR backcoating
Treatment	BLOCKaide® stain repellent

Cleaning Code	W-S
	Standard Care Label W-S. Clean with water based cleaning agents, foam or pure, water free solvents. Vacuuming or light brushing is recommended to prevent dust and soil buildup.

Performance	
Breaking strength (ASTM D5034)	150 lbf min. warp and 120 lbf min. fill
Seam Slippage (ASTM D4034)	75 lbf min. warp and 65 lbf. min. fill
Pilling resistance (ASTM D3511)	Class 4 min.
Colorfastness to light (AATCC 16 Option 3)	Grade 4 min. at 40 hours
Colorfastness to crocking (AATCC 8)	Grade 4 min. dry, Grade 3 min. wet
Abrasion resistance (ASTM D4157)	50,000 double rubs min. - cotton duck

Flammability	
State of CA. Tech. Bulletin, 117-2013 SEC. I	Passes
NFPA 260	Class I

Please do not use for shade master. Colors may vary between dye lots. Whirl and Twilight is a directional fabric. Application testing of this product is recommended. Every effort has been made to ensure color accuracy of the digital images, however, please order a sample before specification. Proudly woven in North America supporting our local communities.



Sauder® Manufacturing Co.
930 W. Barre Road
PO Box 230
Archbold, OH 43502
P: 800.537.1530
F: 419.446.4945
sauderworship.com

Approved for use on:

Pews

Chairs



*Whirl also approved for auditorium